

CHEVRON SERIES

| FEATURES | STANDARD | PLANKS | HERRINGBONE | CHEVRON |
|---|------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Floorcovering | EN 649 | Heterogeneous LVT floorcovering | Heterogeneous LVT floorcovering | Heterogeneous LVT floorcovering |
| Completion | | Matte particle laquer | Matte particle laquer | Matte particle laquer |
| Design | | Wood | Wood | Wood |
| Embossing | | Registered Embossed | Registered Embossed | Registered Embossed |
| Colours | | 4 | 4 | 4 |
| Dimension | EN 427 | 121,90x22,80 cm | 60,96x15,24 cm | 57,15x11,43 cm |
| Bevelling | | All sides | All sides | All sides |
| Content | | 12 pieces (3,345 m ²) | 36 pieces (3,345 m ²) | 52 pieces (3,397 m ²) |
| Article numbers | | 12041 12042 12043 12044 | 6040 6042 6043 6044 | 6541 6542 6543 6544 |
| Weight | EN 430 | ca. 4315 g/m ² | ca. 4315 g/m ² | ca. 4315 g/m ² |
| Thickness | EN 428 | 2,5 mm | 2,5 mm | 2,5 mm |
| Thickness PU | EN 429 | 0,55 mm | 0,55 mm | 0,55 mm |
| Classification | EN 685 | 23, 33, 42 | 23, 33, 42 | 23, 33, 42 |
| Fire classification | EN 13501 | Bfl-S1 | Bfl-S1 | Bfl-S1 |
| Slipresistance | DIN 51130 EN 13893 | R9 DS | R9 DS | R9 DS |
| Weargroup | EN 649 | T | T | T |
| Residual indentation | EN 433 | < 0,1 mm | < 0,1 mm | < 0,1 mm |
| Dimension stability | EN 434 | < 0,1% | < 0,1% | < 0,1% |
| Soundreduction | EN140-8 | ca. 5 dB(A) | ca. 5 dB(A) | ca. 5 dB(A) |
| Thermal conductivity | EN12667 DIN 52612 | 0,02 m ² k/w | 0,02 m ² k/w | 0,02 m ² k/w |
| Electrical conductivity | EN 1081 | app 10 ¹¹ Ohm | app 10 ¹¹ Ohm | app 10 ¹¹ Ohm |
| Suitable for castor chairs | EN 425 | Yes, type W | Yes, type W | Yes, type W |
| Floor heating | EN14041 | Yes, max. 27°C | Yes, max. 27°C | Yes, max. 27°C |
| Colourfastness | ISO 105-B02 | 6> Grade | 6> Grade | 6> Grade |
| Resistance to chemicals | EN 423 EN ISO 26987 | Yes, see 1 | Yes, see 1 | Yes, see ¹ |
| Odor control | ISO 16000-28 | Suisse Norm SNV | Suisse Norm SNV | Suisse Norm SNV |
| AgBB VOC test | | Approved | Approved | Approved |
| REACH regulation (EC) | | 1907/2006 | 1907/2006 | 1907/2006 |
| CE, AGBB, Dibt, Eurofins, Floorscore, A+, ISO9001, ISO14001 | | Yes | Yes | Yes |

¹ Resistance depending on concentration and exposure time, with prolonged action of oils, fats, acids, alkalis and other aggressive chemicals please contact us.

